



Potain MR 295 H16



Mat / Réactions
Masts / Eckdrücke
Masts / Reactions
Mástil / Reacciones
Torre / Reazioni
Tramo / Reações
Композиции
башни / Реакции

MC2.6


2 m



H (m)	5 m	3,33 m
40 m	50,8	9
45 m	49,1	8
50 m	47,5	9
55 m	44,1	7
60 m	42,5	8

P 62 A

F2	227 t
F3	169 t
	254 t
	76 t




H (m)	5 m	3,33 m
35 m	52,1	9
40 m	48,8	9
45 m	45,4	7
50 m	42,1	7
55 m	40,4	6
60 m	38,8	7

ZX 6830

F1	137 t
	157 t
	92 t




ZX 6830



H3 = H




H4 = H - 0,3 m



H (m)	5 m	3,33 m
35 m	47,6	8
40 m	44,3	6
45 m	41	6
50 m	37,6	6
55 m	34,3	4
60 m	32,6	5

V 60 A

F1	137 t
	130 t
	97 t




H (m)	5 m	3,33 m
40 m	50,8	8
45 m	49,1	9
50 m	47,5	8
55 m	42,5	7
60 m	39,1	7

B 60 A




2,45 m



H (m)	5 m	3,33 m
35 m	61,1	10
40 m	57,8	10
45 m	56,1	9
50 m	52,8	9
55 m	51,1	8
60 m	49,5	9

P 800 A


F2	230 t
	302 t
F3	172 t
	254 t
	97 t



H (m)	5 m	3,33 m
35 m	49,1	8
40 m	45,8	8
45 m	42,4	6
50 m	39,1	6
55 m	37,4	5
60 m	37,4	5

ZX 6830


F1	137 t
	163 t
	95 t



H (m)	5 m	3,33 m
35 m	67	11
40 m	63,7	9
45 m	62	10
50 m	58,7	8
55 m	55,4	8
60 m	53,7	7

Y 800 A

F1	149 t
	196 t
	137 t



H (m)	5 m	3,33 m
35 m	61,1	11
40 m	57,8	9
45 m	56,1	10
50 m	52,8	8
55 m	51,1	9
60 m	49,5	8

B 800 B



FR

- Réactions en service
- Réactions hors service



A vide sans lest (ni train de transport) avec flèche et hauteur maximum.

DE

- Reaktionskräfte in Betrieb
- Reaktionskräfte außer Betrieb

Ohne Last, Ballast (und Transportachse), mit Maximalausleger und Maximalhöhe.

EN

- Reactions in service
- Reactions out of service

Without load, ballast (or tren de transporte), with maximum jib and maximum height.

ES

- Reacciones en servicio
- Reacciones fuera de servicio

Sin carga, sin lastre, (ni tren de transporte), flecha y altura máxima.

IT

- Reazioni in servizio
- Reazioni fuori servizio

A vuoto, senza zavorra (ne assali di trasporto) con braccio massimo e altezza massima.

PT

- Reações em serviço
- Reações fora de serviço

Sem carga (nem trem de transporte) sem lastro com lança e altura máximas.

RU

- Реакции при работе
- Реакции в покое

Вес без груза, балласта (или транспортных осей), с максимальной длиной стрелы и максимальной высотой.

MR 295 H16



Mécanismes
Antriebe
Mechanisms
Mecanismos
Meccanismi
Mecanismos
Механизмы

MCZ 8

MR 295 H16 50 Hz										ch - PS hp	kW			IEC 60204-32	
	75 LVF 40 Optima	m/min	0 → 34 → 44 → 76 → 90					0 → 17 → 22 → 38 → 45			75	55			637 m
	100 LVF 40 Optima	m/min	0 → 44 → 56 → 94 → 116					0 → 22 → 28 → 47 → 58			100	75			1136 m
	150 LCC 40	m/min	0 → 70 → 84 → 106 → 140 → 168					0 → 35 → 42 → 53 → 70 → 84			150	110			1092 m
	100 VVF 40	m/min	1 min 40 s								100	75			
ZX 6830	RVF 182 Optima +	tr/min U/min - rpm	0 → 0,8								2 x 12	2 x 9			
	RT 664 A2B 2V	m/min	16 - 32								6 x 7	6 x 5,2			
V 60 A	RT 544 A1 2V R ≥ 13 m	m/min	13,5 - 27								4 x 7	4 x 5,2			
Y 800 A	RT 584 A1 2V	m/min	13,5 - 27								8 x 7	8 x 5,2			

MR 295 H16 60 Hz										ch - PS hp	kW			IEC 60204-32	
	75 LVF 40 Optima	m/min	0 → 34 → 44 → 76 → 90					0 → 17 → 22 → 38 → 45			75	55			637 m
	100 LVF 40 Optima	m/min	0 → 44 → 56 → 94 → 116					0 → 22 → 28 → 47 → 58			100	75			1136 m
	150 LCC 40	m/min	0 → 70 → 84 → 106 → 140 → 168					0 → 35 → 42 → 53 → 70 → 84			150	110			1092 m
	100 VVF 40	m/min	1 min 40 s								100	75			
	RVF 182 Optima +	tr/min U/min - rpm	0 → 0,8								2 x 12	2 x 9			
ZX 6830 	RT 664 A2B 2V	m/min	19 - 38								6 x 8,4	6 x 6,2			
V 60 A 	RT 544 A1 2V R ≥ 13 m	m/min	16 - 32								4 x 8,4	4 x 6,2			
Y 800 A 	RT 584 A1 2V	m/min	16 - 32								8 x 8,4	8 x 6,2			

														75 LVF: 190 kVA 100 LVF: 220 kVA 150 LCC: 270 kVA

														75 LVF: 190 kVA 100 LVF: 220 kVA 150 LCC: 300 kVA

FR

Levage
Relevage
Orientation
Translation
Nous consulter

DE

Heben
Ausleger-Einziehen
Schwenken
Kranfahren
Auf Anfrage

EN

Hoisting
Luffing
Slewing
Travelling
Consult us

ES

Elevación
Elevación de flecha
Orientación
Traslación
Consultarnos

IT

Sollevamento
Brandeggio
Rotazione
Traslazione
Consultateci

PT

Elevação
Inclinação da lança
Rotação
Translação
Consultar-nos

RU

Подъем
Подъем стрелы
Поворот
Перемещение крана
Проконсультируйтесь у нас



Document commercial
non contractuel. Pour
toute information
technique se référer à la
notice correspondante.

Unverbindliches
Vertriebsdokument. Für
technische Informationen,
siehe die entsprechenden
Anweisungen.

This commercial document
is not legally binding. For
any technical information,
please refer to the
corresponding instructions.

Documento comercial
no contractual. Para
cualquier información
técnica, ver la noticia
correspondiente.

Documento commerciale
non vincolante, per tutte
le informazioni tecniche
fare riferimento al
catalogo istruzioni.

Documento comercial não
contratual. Para qualquer
informação técnica
complementar consultar
as respectivas instruções.

Этот коммерческий документ
не является юридически
обязательным. Для получения
технической информации, см.
соответствующие инструкции.

Bigge Crane and Rigging Co.

10700 Bigge Avenue
San Leandro, CA 94577
Phone: (888) 337-BIGGE or (510) 638-8100
Fax: (510) 639-4053
Email: info@bigge.com
Web site: www.bigge.com



Manitowoc - Americas - World Headquarters

2400 S. 44th Street • Manitowoc • WI 54220 USA
Tel: +1 920 684 4410 • Fax: +1 920 652 9778

Manitowoc - Europe, Middle East & Africa

Ecully, France
18, rue de Charbonnières B.P. 173 • 69132 ECULLY Cedex • FRANCE
Tel: +33 (0)4 72 18 20 20 • Fax: +33 (0)4 72 18 20 00

Manitowoc - Asia Pacific

16F Xu Hui Yuan Building,
1089 Zhongshan No.2 Road (S) • Shanghai 200030 China
Tel: +86 21 6457 0066 • Fax: +86 21 6457 4955

MR 295 H16

Réf. 2005 20 MCZ 11

